

寸法 型式・製品番号	H	A	D	P	t	d	d1	d2	E	B	1ヶ当たりの 静的耐荷重(KN)	(参考)静的バネ定数 N/mm	固有振動数 (Hz)	(参考)コイル バネ数	
V1134	01	88	97	131	110	3.2	M12	11	78	-	-	0.4~0.85	65	7~8	1個使い
	02	88	97	131	110	3.2	M12	11	78	-	-	0.65~1.25	95		
	03	88	97	131	110	3.2	M12	11	78	-	-	1.1~1.9	195		
	04	88	97	131	110	3.2	M12	11	78	-	-	1.25~2.7	220		2個使い
	05	88	97	131	110	3.2	M12	11	78	-	-	2.5~4.0	320		
	06	88	97	131	110	3.2	M12	11	78	-	-	3.6~5.6	370		
	25	104	250	-	210	8	M12	13	-	100	100	5.0~8.0	645		4個使い
	26	104	250	-	210	8	M12	13	-	100	100	7.2~11.2	715		
	45	104	200	-	140	8	M12	13	-	-	-	10.0~16.0	1290		
46	104	200	-	140	8	M12	13	-	-	-	14.4~22.4	1430			
V1135	01	88	97	131	110	3.2	M12	11	78	-	-	0.3~0.5	40	5~6	1個使い
	02	88	97	131	110	3.2	M12	11	78	-	-	0.5~0.8	60		
	03	88	97	131	110	3.2	M12	11	78	-	-	0.8~1.25	88		
	04	88	97	131	110	3.2	M12	11	78	-	-	1.25~1.95	170		2個使い
	05	88	97	131	110	3.2	M12	11	78	-	-	1.95~3.1	245		
	06	88	97	131	110	3.2	M12	11	78	-	-	3.1~4.2	300		
	25	104	250	-	210	8	M12	13	-	100	100	3.9~6.2	490		4個使い
	26	104	250	-	210	8	M12	13	-	100	100	6.2~8.4	600		
	45	104	200	-	140	8	M12	13	-	-	-	7.8~12.4	980		
46	104	200	-	140	8	M12	13	-	-	-	12.4~16.8	1200			
V1136	01	138	97	131	110	3.2	M12	11	78	-	-	0.75~1.1	50	3~4	1個使い
	02	138	97	131	110	3.2	M12	11	78	-	-	0.95~1.3	55		
	03	138	97	131	110	3.2	M12	11	78	-	-	1.25~1.6	70		
	04	138	97	131	110	3.2	M12	11	78	-	-	1.6~2.3	105		2個使い
	05	138	97	131	110	3.2	M12	11	78	-	-	2.1~3.1	125		
	06	138	97	131	110	3.2	M12	11	78	-	-	3.0~4.2	170		
	25	154	250	-	210	8	M12	13	-	100	100	4.4~6.2	250		4個使い
	26	154	250	-	210	8	M12	13	-	100	100	6.0~8.3	340		
	45	154	200	-	140	8	M12	13	-	-	-	8.8~12.4	500		
	46	154	200	-	140	8	M12	13	-	-	-	12.0~16.0	680		